

Rechargeable internal batteries
for field use. IP54 rated.

Thermo Scientific Masterflex® P/S Water Sampling Systems



Portable Sampler 950-1990



Composite Sampler 950-3990

Portable Sampler

- Sample rate from 125 to 1100 mL/min; suction lift up to 26 feet.
- IP54-rated when open or closed.
- Variable-speed motor, reversible flow, and prime/purge function.
- Run up to 4 hours on self-contained 12 VDC rechargeable battery, or indefinitely from AC or 12V DC power supply (automotive, etc.).
- Comes complete with Pump Head, AC adapter with 12 ft cord, and 50 feet of High- Performance PVC tubing.
- Dimensions: 41 × 29 × 27 cm (16"H × 11.3"W × 10.5"D).
Weight: 7.5 kg (16.5 lb)

Composite Sampler

- Sampler floats in water for up to 30 minutes when case is closed and latched.
- Easily passes through standard 18-inch diameter manhole.
- Adjustable backlit LCD and glow-in-the-dark keypad help you read the control panel in low-light environments.
- Controls can wait up to 90 days for a remote signal.
- Program operation to meet EPA sampling requirements.
- Comes complete with pump head, tubing, reservoir, and charger.



Portable Sampler

| Ordering Information | | |
|----------------------|--|--------------------|
| Catalog Number | Flow Range | AC Adapter Voltage |
| 950-1990 | 125 to 1100 mL/min (1.98 to 17.4 GPH) | 115 VAC, 50/60 Hz |
| 950-1995 | | 230 VAC, 50/60 Hz |

Composite Sampler

| Ordering Information | | | |
|----------------------|-------------|----------------------|--------------------|
| Catalog Number | Tubing Size | Flow Rate | AC Adapter Voltage |
| VA-950-3990 | 15 | 170 mL/min (2.7 GPH) | 115 VAC, 50/60 Hz |
| VA-950-3995 | 24 | 270 mL/min (4.3 GPH) | 115 VAC, 50/60 Hz |



2 year
warranty